

Google

encoder for generating distortion signal and m

Search Patents

[Advance](#)

Patents Patents 1 - 10 on encoder for generating distortion signal and modulating the buffered bitstream. (0.06 seconds)

▸ List view

[Cover view](#)

▸ Sort by relevance

[Sort by date \(new first\)](#)[Sort by date \(old first\)](#)

▸ Any status

[Issued patents](#)[Applications](#)

[APPLICATION] [Method of embedding a secondary signal in the bitstream of a primary signal](#)

US Pat. 10078975 - Filed Feb 19, 2002

... the **bitstream** of the primary **signal** and an **encoder for generating a distortion signal and modulating the buffered bitstream** of the primary **signal** before ...

[Mixing, coding and decoding devices and methods](#)

US Pat. 6438434 - Filed May 27, 1997 - Yamaha Corporation

By virtue of such behavior, the delta sigma modulator can output **bitstream** data SDO that has been pulse-density- modulated by an analog **signal** waveform ...

[Frequency domain estimation of IQ imbalance in a wireless OFDM direct ...](#)

US Pat. 7184714 - Filed Nov 4, 2003 - Advanced Micro Devices, Inc.

Since certain tones output by the FFT 64 may have encountered fading due to **signal** attenuation and **distortion** 10 on the wireless channel, equalization is

...

[APPLICATION] [Simplified LDPC encoding for digital communications](#)

US Pat. 11201391 - Filed Aug 10, 2005 - Texas Instruments Incorporated

A preferred embodiment of the particular construction of LDPC **encoder** ... channel C adds significant **distortion** and noise to the transmitted analog **signal** , ...

[Layered low density parity check decoding for digital communications](#)

US Pat. 7139959 - Filed Mar 23, 2004 - Texas Instruments Incorporated

Functions through 16 thus convert 10 the input **bitstream** into a serial ... channel C adds significant **distortion** and noise to the transmitted analog **signal**

, ...

[Constant bitrate media encoding techniques](#)

US Pat. 7383180 - Filed Jul 18, 2003 - Microsoft Corporation

The **encoder** formats band information such that information for less perceptually important bands can be incrementally removed from a **bitstream**, if necessary ...

[APPLICATION] [Frequency mapped coding for signal error correction](#)

US Pat. 10676053 - Filed Sep 30, 2003

1 and 2 demonstrate the **distortion** of the QAM PSD from the transmitted **signal** PSD 2 to the received **signal** PSD 4 based on the channel characteristics 6. ...

[APPLICATION] [Accelerating convergence in an iterative decoder](#)

US Pat. 11068256 - Filed Feb 28, 2005 - Texas Instruments Incorporated

After application of the FEC code, bit to symbol **encoder** function 12 groups ... C adds significant **distortion** and noise to the transmitted analog **signal**, ...


[System and method for communicating digital information using time-and ...](#)

US Pat. 6944118 - Filed Aug 20, 2004 - Bandwidth Technology Corp.

2A, 2B, 2C and 2D the incoming waveforms 210 are digitized after **signal** ... a decoder to extract the digital information, and a **generating** mechanism to ...

[APPLICATION] [Hardware-efficient low density parity check code for digital](#)

communications



encoder for generating distortion signal and n

[Advanced Patent Search](#)

[Google Home](#) - [About Google](#) - [About Google Patents](#) - [Google Patents Help](#)

©2010 Google